



HYDROLEGNO FINITURA LUCIDA – *water based woodstains*

Glossy finishing product with water-based acrylic resins suitable for the protection of all wood products for outdoor and indoor use. It forms a film with considerable resistance to stress and external aggressions which maintains during the time high elasticity, thus preventing the phenomena of cracking of the dried film. Non-yellowing and non-flaking.

SPECIFICATIONS

Nature of the pigments: modified acrylic resins in water dispersion, non-yellowing, non-flaking.

Solid content: 43%±1.

Dried product appearance: glossy.

Viscosity at 20 ° C: 15".

Application: brush, spray, roller.

Dilution: ready to use.

Yield: 10-12 sqm/lt for 1 coat, depending on the surface to be treated.

Drying time: to touch 2-3 hours, hardened in depth 18-24 hours.

Recoat: 18-24 hours under normal conditions of temperature and humidity.

METHOD OF USE

Ensure that the surface is thoroughly dried and aged. If necessary, take measures to reconstruct or consolidate the surface by using specific products. Remove any mold, efflorescence and any old peeling paint by brushing or washing. Remove any deposits of dust, smog or other by brushing. Level any irregularities in the surface and treat holes, cracks, crevices and gaps.

- *Never painted wood:* Sand lightly in order to remove any pieces of wood not well anchored; putty imperfections with stucco, if necessary. Sand repair areas and remove dust. Proceed with the application of **Hydrolegno Impregnante (Caf)** in desired color, taking care to sand the surface between one layer and another. Apply one or two coats of **Hydrolegno Finitura Lucida**, depending on the desired protection. For outdoor use it is recommended two coats of application. We do not recommend the application of **Hydrolegno Finitura Lucida (Caf)** on raw wood without having first applied **Hydrolegno Impregnante (Caf)**.

- *Already painted wood:* remove the parts of old paint not well anchored by sanding and brushing; then proceed as above.

CLIMATIC CONDITIONS

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5 ° C and +35 ° C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.



USEFUL TIPS:

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

Protect from frost.

Packaging: 0,750 – 2,5 L.

Color: transparent.

Washing tools: use water immediately after use.

NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

Specification Item

- > Protect all surfaces not subject to application of paint.
- > Preparation of the substrate by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt.
- > Application of two coats of water-based glossy finishing woodstains for the protection of wood **Hydrolegno Finitura Lucida** (Caf), waiting 18-24 hours between coats, after having treated the wooden surface with **Hydrolegno Impregnante** (Caf).
- > All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5°C and +35°C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.