



NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

MARMOS L.P. – lime products

Smooth water-based paint for outdoor based on slaked lime, natural dyes and vegetable and mineral oils. The painted surface with **MARMOS L.P.** presents a nearly uniform color with the presence of light halos that are the hallmark of this product and that makes it look nice and harmonious.

SPECIFICATIONS

Performance: high whiteness, high breathability of the paint surface, reducing the appearance of mold, high yield.

Composition: slaked lime, selected mineral aggregates, natural oils, organic substances not exceeding 5%.

Appearance: mineral matt, veiled with light and shade.

Viscosity: thick paste, stirring it loses some of its consistency

Solid content: 60 ± 2%

Water vapor diffusion : excellent

Weathering resistance : good, no flaking phenomena.

Application: brush, roller.

Dilution: 20% with water.

Yield (2 coats): 0,250-0,300 Kg/sqm, depending on the absorbency of the support.

Drying time: to touch 3 hours, in depth 24 hours in normal conditions of temperature and humidity.

METHOD OF USE

Ensure that the surface is thoroughly dried and aged. If necessary, take measures to reconstruct or consolidate the surface by using specific products. Remove any mold, efflorescence and any old peeling paint by brushing or washing. Remove any deposits of dust, smog or other by brushing. Level any irregularities in the surface and treat holes, cracks, crevices and gaps.

- *New surface:* It is not necessary any preparation, but only moisten the surface with a paintbrush; then apply two coats of **Marmos L.P.** (Caf). Wait for the complete drying between one layer and another.

- *Already painted surface:* remove the old paint with paint remover **Express** (Caf) and remove any scraps; eliminate the cracks with stucco, if necessary; then proceed as above. The maximum coverage is obtained in post-drying phase and not in the application phase. If there are very absorbent surfaces or plaster presents differences in its composition from one area to another (also for patched) it is advisable to apply the primer consolidating Water Fix before lime based paint to minimize any differences in color that may occur on the lime finish coat.

Having regard to the significant differences of application and of physical-chemical nature of the surfaces, no responsibility can be attributed to the producer in case of difficulty of adherence of the product or to different chemical reactions that can occur, even on color and, worse, if there is the presence of moisture, salt and extreme temperatures (hot or cold). It is therefore necessary that the applicator uses all due caution that experience suggests. Remember that the plaster truly breathable compounds with hydraulic lime and without cement are the ideal support for cycles of restoration with diffusive paints.

The technical informations contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.



NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

CLIMATE CONDITIONS

To avoid compromising the optimal appearance and performance of the product we recommended that it be applied only in specific climate conditions:

- Apply to temperatures between +5 °C and +35 °C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in case of humidity;
- Surface must be protected from rain and damp for approximately 48 hours.

USEFUL TIPS

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

Protect from frost.

Packaging: 5 - 20 Kg.

Color: white, Allegro color chart, tints on request.

The coloring is possible with the Tinting System **Allegro**.

Washing tools: use water immediately after use.

Specification Item

- > Protect all surfaces not subject to application of paint.
- > Preparation of the surface by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt. If the surfaces to be treated were covered with organic paints is advisable total removal of these paintings.
- > Application by roller or brush of two coats of lime-based paint **Marmos L.P.** (CAF) waiting at least 24 hours between them, subject to a consumption refers to two coats of 0, 250 - 0,300 Kg/sqm, according to the type of support.
- > All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5 °C and +35 °C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.

The technical informations contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.